



VERIVOLUME QC

Variable Flow Nozzle with Quick Cap

Features

- VeriVolume nozzle molded into Quick Cap fits on standard nozzle bodies.
- Flow rate variable from 1.50 to 10.00 gpm
- Very large droplet
- Wide spray angle
- Provides uniform spray coverage at low pressure and low speed



VVQC140
VeriVolume Quick Cap

Application Chart

PSI	Flow GPM	Droplet size	GALLONS PER ACRE (GPA) - BASED ON FERTILIZER									
			30" SPACING					40" SPACING				
			6 MPH	10 MPH	12 MPH	14 MPH	18 MPH	6 MPH	10 MPH	12 MPH	14 MPH	18 MPH
10	1.5	UC	42.1	25.2	21.0	18.0	14.0	31.6	18.9	15.8	13.5	10.5
15	3.0	UC	84.2	50.5	42.1	36.1	28.1	63.1	37.9	31.6	27.0	21.0
20	4.0	UC	112.2	67.3	56.1	48.1	37.4	84.2	50.5	42.1	36.1	28.1
25	6.0	UC	168.3	101.0	84.2	72.1	56.1	126.2	75.7	63.1	54.1	42.1
30	7.0	UC	196.4	117.8	98.2	84.2	65.5	147.3	88.4	73.6	63.1	49.1
40	8.0	UC	224.4	134.6	112.2	96.2	74.8	168.3	101.0	84.2	72.1	56.1
50	9.0	UC	252.5	151.5	126.2	108.2	84.2	189.3	113.6	94.7	81.1	63.1
60	10.0	UC	280.5	168.3	140.3	120.2	93.5	210.4	126.2	105.2	90.2	70.1

Optimum Spray Height

Spacing	Spray Height
30"	30"
40"	40"

High-flow nozzle bodies are recommended